

Package: ausplotsR (via r-universe)

September 13, 2024

Type Package

Title TERN AusPlots Australian Ecosystem Monitoring Data

Version 2.0.6

Date 2023-12-20

Maintainer Greg Guerin <ggueri01@gmail.com>

Depends R (>= 3.1.0), ggplot2, mapdata

Suggests knitr, rmarkdown, markdown, formatR, sf

Imports vegan, plyr, R.utils, httr, jsonlite, gtools, jose, betapart, curl, r2r, stringr, progress

Description Extraction, preparation, visualisation and analysis of TERN AusPlots ecosystem monitoring data. Direct access to plot-based data on vegetation and soils across Australia, including physical sample barcode numbers. Simple function calls extract the data and merge them into species occurrence matrices for downstream analysis, or calculate things like basal area and fractional cover. TERN AusPlots is a national field plot-based ecosystem surveillance monitoring method and dataset for Australia. The data have been collected across a national network of plots and transects by the Terrestrial Ecosystem Research Network (TERN - <<https://www.tern.org.au>>), an Australian Government NCRIS-enabled project, and its Ecosystem Surveillance platform (<<https://www.tern.org.au/tern-land-observatory/ecosystem-surveillance-and-environmental-monitoring/>>).

License GPL-3

VignetteBuilder knitr

RoxygenNote 7.2.3

Encoding UTF-8

Repository <https://ternaustralia.r-universe.dev>

RemoteUrl <https://github.com/ternaustralia/ausplotsr>

RemoteRef HEAD

RemoteSha 6eee93077e2096e6b90bb6638442fa4770fbcf6b

Contents

ausplotsR-package	2
ausplots_trajectory	5
ausplots_visual	7
basal_area	10
fractional_cover	11
get_ausplots	13
growth_form_table	16
optim_species	19
plot_opt	22
single_cover_value	24
species_list	26
species_table	28

Index	31
--------------	-----------

ausplotsR-package	<i>Live extraction, preparation, visualisation and analysis of TERN Aus-Plots ecosystem monitoring data.</i>
-------------------	--

Description

Through ausplotsR, users can directly access plot-based data on vegetation and soils across Australia, including physical sample barcode numbers. Simple function calls extract the data and merge them into species occurrence matrices for downstream analysis or calculate things like basal area and fractional cover.

ausplotsR whas been tested for R version 4 (recommended).

Details

Package: ausplotsR
 Type: Package
 Version: 2.0.6
 Date: 2023-12-20
 License: GPL-3

TERN AusPlots is a national field plot-based ecosystem surveillance monitoring method and dataset for Australia. A standardised national network of plots enables consistent ecological assessment and monitoring. The data are open access under Creative Commons – Attribution 4.0 International (CC BY 4.0), and have been collected across a national network of plots and transects by the Terrestrial Ecosystem Research Network (TERN - <https://www.tern.org.au>), an Australian Government NCRIS-enabled project, and its Ecosystem Surveillance platform (<https://www.tern.org.au/tern-land-observatory/ecosystem-surveillance-and-environmental-monitoring/>).

The AusPlots survey method is made up of a series of individual modules, which are described in full in the protocols manual (White et al. 2012, Sparrow et al. 2020). Data from the following modules can currently be accessed through ausplotsR: plot selection and layout; vascular plant vouchers; point intercept; basal area; structural summary; and soils. Field data are recorded directly onto mobile (tablet) devices before being stored in cloud-based server infrastructure.

Method summaries:

Plot layout: 1 ha (100 x 100 m) plots are permanently marked over a homogenous patch of terrestrial vegetation.

Soil sampling: soils are characterised in a pit at the SW corner of the plot to 1 m depth and 500 g samples are collected at 10 cm depth intervals; soil bulk density is measured; nine soil subsites are located across the plots and 500 g samples are taken at 10 cm depths to 30 cm. Additionally, 200 g surface soil (~3 cm depth) samples are taken at the nine subsites and silica-dried for metagenomic analysis.

Structural summary: the dominant species in three vegetation strata (lower, middle and upper) are identified visually by the observer. The vegetation is then categorised into MVGs according to the Australian National Vegetation Information System (NVIS 2017).

Vascular plant vouchers: all vascular plants within the plot are detected visually, with a herbarium voucher taken for each unique taxon, which is assigned a barcode and identified then permanently stored in a herbarium. Additionally, silica-dried material is sampled from each species for genetic and isotopic analysis, and five replicate samples are taken for dominant species. Bryophytes are sometimes recorded opportunistically (e.g. when prominent) but full diversity is not systematically collected.

Point-intercept : 10 x 100 m long transects are laid out within the plot in a grid pattern. A staff with laser pointer and densiometer is used to record species, growth form and height plus substrate type every 1 m along the transects, resulting in a total of 1010 (10 x 101) point-intercept hits for the plot.

Basal wedge : a basal wedge is used to determine the basal area of trees and shrubs at 1.3 m, with measures of hits per species taken at nine locations across the plot.

Additional modules in the AusPlots method not available through this package include: full DGPS coordinate data (only the coordinates of the SW corner are provided here), photo panoramas, Leaf Area Index.

Acknowledging TERN AusPlots data in publications:

It is important that users of data extracted via ausplotsR acknowledge TERN, the AusPlots dataset and ausplotsR by including an appropriate citation in the Acknowledgments or References section of any published papers/reports/theses that make use of the data. To make this easy, a data citation is automatically generated when you extract data (see `get_ausplots`). It has the following format:

TERN ("year") AusPlots ecosystem surveillance monitoring dataset (URL: <http://aekos.org.au/>). Obtained via the ausplotsR R package (URL: <https://github.com/ternaustralia/ausplotsR>), accessed "day month year".

To cite the ausplotsR package itself and the functions it contains, enter: `citation('ausplotsR')`, or see links to citable archived versions with DOI at <https://github.com/ternaustralia/ausplotsR>.

Key functions in the ausplotsR package:

[get_ausplots](#) : This function is the starting point for accessing data through the ausplotsR package for the following survey modules: Site information; Vegetation point intercept; Vegetation vouchers; Basal wedge; Vegetation structural summaries; Soils and soil samples information.

[ausplots_visual](#) : Quick maps and demonstration graphics for AusPlots.

[species_table](#) : Species occurrence matrices for AusPlots.

[growth_form_table](#) : Plant growth form occurrence matrices for TERN AusPlots.

[fractional_cover](#) : Fractional cover based on TERN AusPlots data.

[basal_area](#) : Basal area of tree trunks in TERN AusPlots.

[single_cover_value](#) : Vegetation cover in TERN AusPlots by height and growth form subsets.

[species_list](#) : Simplified plant species lists for TERN AusPlots based on verified vouchers.

[ausplots_trajectory](#) : Visualisation of species composition and community index revisit trajectories.

[optim_species](#) : Species accumulation optimisation for community data including TERN AusPlots.

Author(s)

Greg Guerin, Tom Saleeba, Samantha Munroe, Bernardo Blanco-Martin, Irene Martin-Fores, Walid Al Naim, Andrew Tokmakoff

Maintainer: Greg Guerin <ggueri01@gmail.com>

References

Guerin, G. R., Sparrow, B., Tokmakoff, A., Smyth, A., Leitch, E., Baruch, Z., & Lowe, A. J. (2017). Opportunities for integrated ecological analysis across inland Australia with standardised data from Ausplots Rangelands. *PLoS ONE*, **12**, e0170137.

Munroe, S., Guerin, G.R., Saleeba, T., Martin-Fores, M., Blanco-Martin, B., Sparrow, B. & Tokmakoff, A. (2021). ausplotsR: An R package for rapid extraction and analysis of vegetation and soil data collected by Australia's Terrestrial Ecosystem Research Network. *Journal of Vegetation Science*, **32**, e13046.

NVIS Technical Working Group (2017). Australian Vegetation Attribute Manual: National Vegetation Information System, Version 7.0. Department of the Environment and Energy, Canberra. Prep by Bolton, M.P., deLacey, C. and Bossard, K.B. (Eds)

Sparrow, B., Foulkes, J., Wardle, G., Leitch, E., Caddy-Retalic, S., van Leeuwen, S., Tokmakoff, A., Thurgate, N., Guerin, G.R. and Lowe, A.J. (2020). A vegetation and soil survey method for surveillance monitoring of rangeland environments. *Frontiers in Ecology and Evolution*, **8**, 157.

Tokmakoff, A., Sparrow, B., Turner, D., & Lowe, A. (2016). AusPlots Rangelands field data collection and publication: Infrastructure for ecological monitoring. *Future Generation Computer Systems*, **56**, 537-549.

White, A., Sparrow, B., Leitch, E., Foulkes, J., Flitton, R., Lowe, A. J., & Caddy-Retalic, S. (2012). AUSPLOTS rangelands survey protocols manual. University of Adelaide Press.

See Also

[get_ausplots](#)

Examples

```
## Not run:
#load package:
library(ausplotsR)

#get data for selected plots:
my.data <- get_ausplots(my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002"),
  basal.wedge=TRUE, structural_summaries=TRUE)

#view module:
my.data$struct.summ

#get site info for all available plot visits:
get_ausplots()

#get a species by sites table:
my.data <- get_ausplots(my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002"),
  veg.PI=TRUE)

species_table(my.data$veg.PI, m_kind="percent_cover", cover_type="PFC",
  species_name="SN")

## End(Not run)
```

ausplots_trajectory *Visualisation of species composition and community index revisit trajectories*

Description

Generates 2D plots visualising the trajectory of species composition (PCoA) and diversity (scatterplot or time series) for revisit series. Trajectories are calculated from the TERN AusPlots point intercept module (`$veg.PI`) as generated by [get_ausplots](#) and other pre-processing functions.

Usage

```
ausplots_trajectory(my.ausplots.object, choices = c("PCoA", "diversity"),
  min.revisits = 3, plot_select = NULL, outfile = NULL)
```

Arguments

<code>my.ausplots.object</code>	Input raw data object (list) as generated in a call from the get_ausplots function. See Details.
<code>choices</code>	Character. User selection of PCoA and/or diversity plots. Both are generated by default.
<code>min.revisits</code>	Integer. Minimum number of revisits required to include a plot.

plot_select	Optional character vector of AusPlots plot IDs (site_location_name) to request data for a specific set of plots. Note PCoA will not run on one or very few plots/surveys.
outfile	Optional file path and name to which the output pdf file is written.

Details

This function primarily applies the functionality of R package *ecotraj* (De Cáceres et al. 2019; Sturbois et al. 2021) to the TERN AusPlots vegetation point intercept data by including the required pre-processing of the raw data and modifications to the output plot format. The function is intended as a rapid, visual means to compare revisit trajectories in species composition and diversity (or other community indices) among sites. For in-depth change/trajectory analysis, users are directed to work with the raw data and the extensive functionality in *ecotraj* or other approaches.

The default graphical outputs require `$site.info`, to order visits by date, and `$veg.PI`, for plant species abundance, in the AusPlots data extract. User-generated community indices (any single value per survey/`$site_unique`) can be plotted in place of diversity if `$community.indices` appears in the `my.ausplots.object`. This table must have a `$site_unique` column matching surveys in `$site.info` and any number of additional columns representing any community indices intended for plotting out over time. See Examples.

Two output options are available. 'PCoA' displays the first two axes (and their respective deviance explained as axis labels) of a metric ordination based on species abundances and so shows the trajectory of plots in species composition space. Similar trajectories on the plot implies parallel trends in species presence and abundance.

Next, 'diversity' by default displays a simple scatterplot with trajectories between revisits. The function presently computes species richness and Shannon diversity metrics using the *vegan* package (Oksanen et al. 2022) and displays these as trajectories on a 2D scatterplot, as well as individually against year. By adding a data table `$community.indices` to those available via `get_ausplots`, users can also plot out the trajectory of other bespoke community level indices. For > 2 indices, only individual plots against year of survey are generated.

Note that revisits (and revisit series > 2) are available only for a subset of the full plot network and that `ausplots_trajectory` may display trajectories better for targeted sets of plots.

Value

Plots are written to a pdf file to ensure consistent formatting, saved by default in the working directory.

Author(s)

Greg Guerin

References

- De Cáceres, M., Coll, L., Legendre, P., Allen, R.B., Wiser, S.K., Fortin, M.J., Condit, R. & Hubbell, S. (2019). Trajectory analysis in community ecology. *Ecological Monographs* 89: e01350
- Oksanen J, Simpson G, Blanchet F, Kindt R, Legendre P, Minchin P, O'Hara R, Solymos P, Stevens M, Szoecs E, Wagner H, Barbour M, Bedward M, Bolker B, Borcard D, Carvalho G, Chirico M,

De Cáceres M, Durand S, Evangelista H, FitzJohn R, Friendly M, Furneaux B, Hannigan G, Hill M, Lahti L, McGlenn D, Ouellette M, Ribeiro Cunha E, Smith T, Stier A, Ter Braak C, Weedon J (2022). `_vegan: Community Ecology Package_`. R package version 2.6-4, <<https://CRAN.R-project.org/package=vegan>>.

Sturbois, A., De Cáceres, M., Sánchez-Pinillos, M., Schaal, G., Gauthier, O., Le Mao, P., Ponsoero, A., & Desroy, N. (2021). Extending community trajectory analysis : New metrics and representation. *Ecological Modelling* 440: 109400

See Also

[get_ausplots](#)

[ausplots_visual](#)

Examples

```
## Not run:
#Extract site data first:
my.data <- get_ausplots()

#Extract vegetation point intercept data for plots with revisits
#Here, subsetting my.Plots_IDs to revisits in one bioregion
my.data <- get_ausplots(veg.PI = TRUE,
my.Plot_IDs = unique(subset(my.data$site.info, visit_number > 1
& bioregion_name == "MAC", select=site_location_name))[,1])

#Display species composition trajectory for all plots with at least 3 revisits
ausplots_trajectory(my.data, choices = "PCoA")

#Display fractional cover trajectories (community index example)
my.data$community.indices <- fractional_cover(my.data$veg.PI)[,c("site_unique",
"bare", "brown", "green")]

ausplots_trajectory(my.data, choices = "diversity")

## End(Not run)
```

ausplots_visual

Graphical illustration of sample TERN AusPlots data

Description

Generates a set of graphical displays representing TERN AusPlots data based on geographic locations and vegetation attributes from the plot-based point intercepts (as generated by [get_ausplots](#) and other pre-processing functions).

Usage

```
ausplots_visual(my.ausplots.object = NULL, map = TRUE, map.attribute = TRUE,
fraction.pie = TRUE, growthform.pie = TRUE, cumulative.cover = TRUE,
whittaker = TRUE, outfile=NULL, max.plots = 5)
```

```
map_ausplots(my.ausplots.object)
```

Arguments

<code>my.ausplots.object</code>	Optional (but required for <code>map_ausplots</code>) input raw data object as generated in a call from the <code>get_ausplots</code> function. The default graphical outputs require <code>\$site.info</code> (for locations) and <code>\$veg.PI</code> (for vegetation attributes) to be included in the AusPlots data extract.
<code>map</code>	Logical, whether to include a basic map of site locations in the context of Australia.
<code>map.attribute</code>	Logical, whether to include a map depicting site locations in Australia coded by cover of trees over 5 m high.
<code>fraction.pie</code>	Logical, whether to include pie charts depicting <code>fractional_cover</code> .
<code>growthform.pie</code>	Logical, whether to include pie charts depicting relative cover of plant growth forms.
<code>cumulative.cover</code>	Logical, whether to include graphs of cumulative cover estimates by species as point intercepts are taken across each AusPlot.
<code>whittaker</code>	Logical, whether to include Whittaker plots depicting species abundance distributions.
<code>outfile</code>	Optional file path and name to which the output pdf file is written.
<code>max.plots</code>	Maximum number of sites for which to display individual graphics panels. By default, <code>max.plots</code> sites are selected randomly. If you provide existing AusPlots data, <code>max.plots</code> sites are processed (in order) whenever <code>fractional.pie</code> or <code>cumulative.cover</code> are selected, because those calculations can be slow across a large number of plots.

Details

By default, extracts sample data, allowing the user to explore the dataset in a single call, or to easily visualise an extracted AusPlots dataset. Included in the default demonstration plots are maps of plot locations with and without coding by tree cover, and then a set of four panels for a smaller sample of AusPlots, depicting data from the main vegetation tables in the package, i.e., fractional cover, growth form cover, species cover and species relative abundance. This function is intended as a simple demonstration of the data available. Refer to TERN tutorials for many other ways to visualise and explore AusPlots.

Value

Plots are written to a pdf file to ensure consistent formatting, saved by default in the working directory.

Author(s)

Greg Guerin, Bernardo Blanco-Martin

References

Blanco-Martin, B. (2019) Tutorial: Understanding and using the 'ausplotsR' package and AusPlots data. Terrestrial Ecology Research Network. Version 2019.04.0, April 2019. <https://github.com/ternaustralia/TERN-Data-Skills/>

Guerin, G.R., Sparrow, B., Tokmakoff, A., Smyth, A., Leitch, E., Baruch, Z., Lowe, A.J. (2017) Opportunities for integrated ecological analysis across inland Australia with standardised data from AusPlots Rangelands. *PLoS ONE* **12**, e0170137.

Whittaker, R.H. (1965) Dominance and diversity in land plant communities: numerical relations of species express the importance of competition in community function and evolution. *Science*, **147**, 250-260.

See Also

[get_ausplots](#)

[fractional_cover](#)

[growth_form_table](#)

[single_cover_value](#)

[species_table](#)

[ausplots_trajectory](#)

Examples

```
## Not run:
#Default output
#Plot locations; visualisations for 5 random plots (including revisits):
ausplots_visual()

#Map tree cover only for all sites:

#Extract data first:
my.data <- get_ausplots(veg.PI=TRUE)

#Set maximum number of plots to all available in the veg.PI data:
ausplots_visual(my.data, map = FALSE, map.attribute = TRUE,
fraction.pie = FALSE, growthform.pie = FALSE, cumulative.cover = FALSE,
whittaker = FALSE, outfile = "AusPlots_treeCover.pdf",
max.plots=length(unique(my.data$veg.PI$site_location_name)))

## End(Not run)
```

basal_area	<i>Basal area of tree trunks in TERN AusPlots</i>
------------	---

Description

Calculates basal area (or number of basal wedge hits) for each plot, using the raw basal wedge data returned from `get_ausplots`.

Usage

```
basal_area(veg.basal, by.spp=FALSE, by.hits=FALSE,
           species_name=c("SN", "HD", "GS"))
```

Arguments

<code>veg.basal</code>	Raw basal wedge data generated from get_ausplots .
<code>by.spp</code>	Set to TRUE to get values per individual species in plots rather than combined values per plot.
<code>by.hits</code>	Set to TRUE to return the number of individual basal wedge hits rather than basal area per se.
<code>species_name</code>	If <code>by.spp=TRUE</code> , set to "SN" to use "standardised_names" (the default), "HD" to use "herbarium_determination", and "GS" to use "genus_species". See details for explanation of each setting.

Details

Stand basal area is the cross-sectional area of tree trunks per unit area, and is measured at each plot using a basal wedge sweep. Measurement is by species at nine points, and basal area (number of hits at a defined wedge angle multiplied by the basal wedge factor) is averaged across them (Finch 1957). Raw tree stem hits are also recorded, noting that the number of hits is dependent on the basal wedge factor in use. Note that species-level estimates of basal area (if requested in the function) may be unstable if there were fewer than 7 hits of that species.

`species_name` provides multiple options for calculating basal area if `by.spp=TRUE`. For example, if `species_name="HD"`, the function will use the "herbarium_determination" provided by state herbaria to identify unique species. "herbarium_determination" are made to the lowest possible taxonomic rank, which may be the family, genus, species, subspecies or variety. If `species_name="SN"`, the default, the function will use the the "standardised_name" to identify unique species. Values are based on the `veg.PI$herbarium_determination` but have been matched to the accepted scientific name according to the Australian Plant Census (APC: <https://www.anbg.gov.au/cpbr/program/hc/hc-APC.html>) and the Australian Plant Name Index (APNI: <https://www.anbg.gov.au/cpbr/program/hc/hc-APNI.html>). The standardised name field therefore helps to ensure taxonomic consistency. It excludes any records that don't match the APC. If `species_name="GS"`, only the standardised genus species rank ("genus_species" in the `veg.basal` input table) is used to identify species. `species_name="GS"` maximises consistency in species comparisons between plots, but reduces the taxonomic detail.

Value

Returns a dataframe with rows for plots (or species by plots if by . spp=TRUE) and basal area (m²/ha) or hit scores as mean per plot/species across the 9 sweep points. Species means (if selected) are mean across all 9 sweep points, even if a species is recorded at fewer points.

Author(s)

Greg R. Guerin, Samantha E.M. Munroe

References

Finch, H.D.S. (1957) Plotless enumeration with angle gauges. *Forestry* 30, 173-192.

See Also

[get_ausplots](#)

Examples

```
## Not run:
#get basal wedge data for selected plots:
my.data <- get_ausplots(my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002"),
  site_info=FALSE, basal.wedge=TRUE)

#calculate basal area:
basal_area(my.data$veg.basal)

## End(Not run)
```

fractional_cover	<i>Fractional cover based on TERN AusPlots data.</i>
------------------	--

Description

Calculates fractional cover (i.e., the proportional cover of green vegetation, dead vegetation and bare substrate) based on plot-based point-intercept data from AusPlots (as generated by [get_ausplots](#)).

Usage

```
fractional_cover(veg.PI, ground_fractional=FALSE, in_canopy_sky=FALSE)
```

Arguments

veg.PI	The input raw point-intercept data as generated in the get_ausplots function.
ground_fractional	Logical. Set to TRUE to calculate fractional GROUND cover.
in_canopy_sky	Logical. Set to TRUE to include in green fraction, thereby calculating opaque canopy cover.

Details

Cover fractions are assigned according to the following:

'Green' or 'photosynthetic vegetation' is living vascular plant cover.

'Brown' or 'non-photosynthetic vegetation' is either vascular plant cover scored as 'dead' or substrate scored as litter, coarse woody debris or cryptogam (see below) that has no other veg cover.

'Bare' or 'bare ground' is substrate that is rock, outcrop, gravel or bare soil with no veg cover.

A height rule is applied so that coding to green/brown/bare of the uppermost substrate/vegetation stratum hit at a given point intercept location overrides the others. That is, a dead tree overrides a living shrub beneath and vice versa; substrate coding is overridden by any vegetation cover etc. This means for each of the (usually) 1010 intercepts, there is a single coding and percentage is the number of hits assigned to each fraction, divided by the total number of PIs taken (usually 1010 but can vary) times 100.

There is an option via argument 'ground_fractional' to calculate fractional ground cover - the same concept applied to only grasses (hummock, tussock, other); sedge; rush; forb; fern; and vine plant growth forms. Presently, cryptogam cover is excluded and included in the non-photosynthetic fraction.

'In canopy sky' is excluded by default (only the substrate is considered for those hits) and applies only to regular fractional cover (as trees are excluded in the green fraction for ground fractional cover by default).

Currently, cryptogam substrate is assigned to the non-photosynthetic fraction.

Occasionally substrate type was not collected ('NC') or could not be assigned to one of the above categories ('Unknwn'), in which case a percent cover will be returned under an 'NA' fraction if there was no veg cover above those points.

Value

Returns a data frame in which plots are rows, columns are fractions (bare, brown, green and NA) and values are percent cover.

Author(s)

Greg Guerin

See Also

[get_ausplots](#)

Examples

```
## Not run:
#get veg.PI data for selected plots:
my.data <- get_ausplots(my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002"),
  veg.PI=TRUE, site_info=FALSE)

#calculate fractional cover:
fractional_cover(my.data$veg.PI)

## End(Not run)
```

get_ausplots

Extract AusPlots data for sites, soils and vegetation

Description

This function is the starting point for accessing data through the ausplotsR package.

Usage

```
get_ausplots(my.Plot_IDs="none", site_info=TRUE, structural_summaries=FALSE,
  veg.vouchers=FALSE, veg.PI=FALSE, basal.wedge=FALSE, soil_subsites=FALSE,
  soil_bulk_density=FALSE, soil_character=FALSE, plot_search=NULL,
  bounding_box="none", herbarium_determination_search=NULL, family_search=NULL,
  standardised_name_search=NULL, dictionary=FALSE)
```

Arguments

my.Plot_IDs	Optional character vector of AusPlots plot IDs (One of site_location_name or site_unique fields) to request data for specific set of plots/visits.
site_info	Whether site summary data are required (includes plot and visit details, landform data, geographic coordinates, notes etc). Default is to include.
structural_summaries	Whether site vegetation structural summaries are required.
veg.vouchers	Whether vegetation vouchers data are requested - contains a complete set of species records for the plot determined by a herbarium plus ID numbers for silica-dried tissue samples.
veg.PI	Whether point-intercept data are requested; includes data on substrate, plant species, growth form and height etc at each of (typically) 1010 points per plot.
basal.wedge	Whether basal wedge data raw hits are required to enable calculation of basal area by species by plot.
soil_subsites	Whether soil subsite information is required. This includes information on what soil and soil metagenomics samples were taken at nine locations across the plot and their identification barcode numbers.
soil_bulk_density	Whether soil bulk density data are required.
soil_character	Whether soil characterisation and sample ID data at 10 cm increments to a depth of 1 m are required.
plot_search	Optional character string filter for selecting AusPlots based on wildcard/partial match to the site_location_name.
bounding_box	An additional optional spatial filter for selecting AusPlots based on a rectangular box, in the format of e.g. c(xmin, xmax, ymin, ymax). AusPlots location data are in longlat, therefore x is the longitude and y is the latitude of the box/extent object. e.g., c(120, 140, -30, -10).

herbarium_determination_search	Optional character string filter for selecting AusPlots based on the presence of a genus or species as recorded in the "herbarium_determination" column. See details for search term settings.
family_search	Optional character string filter for selecting AusPlots based on the presence of a plant family as recorded in the 'family' column. Will be NA if no family identification was possible. See details for search term settings.
standardised_name_search	Optional character string filter for selecting AusPlots based on the presence of a genus and/or species as recorded in the 'standardised_name' column. Will be NA if no genus rank (at minimum) was possible. See details for search term settings.
dictionary	Whether the metadata variable dictionary is required. Provides a table that describes many of the variables and values in each data frame.

Details

By default, the function will extract and compile a site information table including details of all available plot visits. Arguments allow the user to select sites by plot ID and visit codes, geographic bounding box, or species, and select which modules data are drawn from. Partial/wildcard site code matches are enabled in the `plot_search` argument, and further spatial filtering of sites from a master list is possible by using the 'bioregion_name', 'state', and spatial coordinate fields in the site table. Additional tables such as vegetation vouchers, point intercept modules and soil attributes can be requested by setting the desired modules to 'TRUE'.

The datasets returned by the function are used directly by further formatting and analysis functions in `ausplotsR` (such as `species_table` to generate a species by sites matrix for community analysis), making it simple to go from raw data extract to ecological analysis.

AusPlots surveys are identified by a plot ID called `site_location_name` and unique visit number, that are combined to identify a unique measurement for sites with repeat visits, identified in the extracted data tables as 'site_unique'.

"herbarium_determination_search", "family search", and "standardised_name_search" search terms are not case sensitive and do not require an exact taxonomic match (e.g. "Eucalyptus moderata", "Eucalyptus", and "euca" are all acceptable search terms). If `veg.vouch=TRUE`, `veg.vouch` will return a data frame that only includes voucher records that match the species or family search. If `veg.PI=TRUE`, `veg.PI` will return point intercept data for all plots where the species or family occurs. If `basal.wedge=TRUE`, `veg.basal` will return a dataframe that only includes the raw basal wedge data of records that match the species or family. For all other `data.frames`, `get_ausplots` will return data for all the plots where the species or family occurs.

herbarium determinations are provided by state herbaria and are the most commonly used scientific names in the given state. However, scientific names may differ between states and with international databases due to disagreements on taxonomy/nomenclature. Herbarium determinations are made to the lowest possible taxonomic rank, which may be the family, genus, species, subspecies or variety.

`standardised_name_search` values are based on the `veg.PI$herbarium_determination` but have been matched to the accepted scientific name according to the Australian Plant Census (APC: <https://www.anbg.gov.au/cpbr/program/hc/hc-APC.html>) and the Australian Plant Name Index (APNI: <https://www.anbg.gov.au/cpbr/program/hc/hc-APNI.html>). The standardised name field therefore

helps to ensure taxonomic consistency. `standardised_name_search` determinations are made to the lowest possible taxonomic rank, which may be the family, genus, species, subspecies or variety. It excludes any records that don't match the APC. Additional taxonomic fields based on the `standardised_name` are listed as separate columns in `veg.PI`, `veg.vouch`, and `veg.basal` data tables.

The metadata variable dictionary returned by `dictionary=T` may not include all of the the variables and values in each data frame, but will be expanded over time.

Value

Returns a list with following elements, depending on the AusPlots modules requested in the function call.

<code>\$site.info</code>	Data frame with basic site information including location.
<code>\$struct.summ</code>	Data frame with vegetation structural summaries for each plot.
<code>\$veg.vouch</code>	Data frame with rows for each voucher and information on species determinations and silica-dried tissue samples.
<code>\$veg.PI</code>	Data frame with individual point-intercept data.
<code>\$veg.basal</code>	Data frame with compiled raw basal wedge hit data.
<code>\$soil.sub</code>	Data frame with details of soil subsites within each plot including sample IDs.
<code>\$soil.bulk</code>	Data frame with raw bulk density data from each plot.
<code>\$soil.char</code>	Data frame with soil characterisation data from the 1 m pit at the SW corner of each plot.
<code>\$metadata.dictionary</code>	Data frame that lists and describes each variable and corresponding values in each data frame.
<code>\$citation</code>	Auto-generated citation for the data extracted. Please cite <code>ausplotsR</code> and the TERN AusPlots data you use.

Author(s)

Greg Guerin, Andrew Tokmakoff, Tom Saleeba, Samantha Munroe

See Also

[species_table](#)

Examples

```
## Not run:
#get data for selected plots:
my.data <- get_ausplots(my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002")
, basal.wedge=TRUE, structural_summaries=TRUE)

#View module:
my.data$struct.summ

#Get data citation and extraction date info:
my.data$citation
```

```

#Get site info for all available plots:
my.data <- get_ausplots()

##Subset site records to plots with revisits only
#vector of plots with revisits
revisited_plots <- unique(my.data$site.info$site_location_name[
which(my.data$site.info$visit_number > 1)])

#subset site table to revisited plots
revisited_site.info <- my.data$site.info[
which(my.data$site.info$site_location_name

#Get voucher records for "Eucalyptus moderata" using "herbarium_determination":
Eucalyptus_moderata <- get_ausplots(site_info=FALSE, veg.vouchers=TRUE,
herbarium_determination_search="Eucalyptus moderata")

head(Eucalyptus_moderata$veg.vouch, 10)

#Get veg voucher records for all species in the family "Myrtaceae"
Myrtaceae <- get_ausplots(site_info=FALSE, veg.vouchers=TRUE, family_search="Myrtaceae")
head(Myrtaceae$veg.vouch,10)

## End(Not run)

```

growth_form_table *Plant growth form occurrence matrices for TERN AusPlots*

Description

Generates occurrence matrices for NVIS plant growth forms in plots as desired based on presence/absence, percent cover or species richness (i.e., the number of species assigned to a particular growth form). The input is a data frame of raw point intercept data from AusPlots generated using the [get_ausplots](#) function. Alternatively, cover by strata can be calculated.

Usage

```

growth_form_table(veg.PI, m_kind=c("PA", "percent_cover", "richness"),
cover_type=c("PFC", "OCC"), cumulative=TRUE, by_strata=FALSE,
species_name=c("SN", "HD", "GS"))

```

Arguments

veg.PI	The input raw point intercept data generated by get_ausplots
m_kind	The desired scoring method: binary (presence/absence; PA), percent cover or species richness.

cover_type	A choice between PFC: 'projected foliage cover' and OCC: 'opaque canopy cover' and only applies to percent_cover. If 'PFC', the default, is selected (suitable as an abundance or cover measure for most applications), hits scored as 'in canopy sky' are removed, whereas they are retained as cover for that species for 'OCC' (suitable for application such as comparisons to remotely sensed cover).
cumulative	Logical. Should the cover of each growth form be calculated cumulatively across species (i.e., the sum of species covers in that growth form category; the default) or as absolute cover (percent of points where that growth form was hit)? Ignored except when m_kind="percent_cover".
by_strata	Logical. If set to TRUE, cover is calculated by strata (as defined by growth forms). Ignored except when m_kind="percent_cover".
species_name	Select "SN" to use "standardised_names" (the default), "HD" to use "herbarium_determination", and "GS" to use "genus_species". See details for an explanation of each setting.

Details

Probably the most useful data output from this function is the matrix of plant growth forms against sites with percent cover. This could be used in manova, ordination, classification etc. It also provides a multivariate structural and functional response variable.

species_name provides multiple options for calculating plant growth form cover. If species_name="HD", the function will use the "herbarium_determination" provided by state herbaria to identify unique species. "herbarium_determination" are made to the lowest possible taxonomic rank, which may be the family, genus, species, subspecies or variety. If species_name="SN", the default, the function will use the the "standardised_name" to identify unique species. Values are based on the veg.PI\$herbarium_determination but have been matched to the accepted scientific name according to the Australian Plant Census (APC: <https://www.anbg.gov.au/cpbr/program/hc/hc-APC.html>) and the Australian Plant Name Index (APNI: <https://www.anbg.gov.au/cpbr/program/hc/hc-APNI.html>). The standardised name field therefore helps to ensure taxonomic consistency. It excludes any records that don't match the APC. If species_name="GS", only the standardised genus species rank ("genus_species" in the veg.PI input table) is used to identify species. species_name="GS" maximises consistency in species comparisons between plots, but reduces the taxonomic detail.

Note sometimes the same species is recorded with different growth forms in a plot and therefore the rowSums of the occurrence matrix when m_kind is set to "richness" can be higher than the observed species richness because the same species can count towards the weights for multiple growth forms.

By default, cumulative percent cover (percent of hits out of total number of point intercepts) is returned, meaning multiple species of the same growth form hit at a point add to the score, which can therefore exceed 100 percent. If cumulative=FALSE, non-cumulative cover is returned, whereby only one hit is counted per growth form per point-intercept, with a maximum of 100.

If by_strata=TRUE, returns percent cover of three pre-defined strata: Upper, Mid and Lower, based on the crude assignment of growth forms such that Upper includes "Tree Mallee", "Tree/Palm", "Tree-fern", "Epiphyte"; Mid includes "Shrub Mallee", "Shrub", "Grass-tree", "Chenopod", "Heath-shrub"; and Lower includes "Tussock grass", "Forb", "Vine", "Hummock grass", "Fern", "Sedge", "Rush". The argument cumulative still applies for cover by strata, where the default (TRUE) is to calculate the cumulative cover of species in each stratum. Absolute cover (i.e., maximum value of 100) of strata can be calculated by setting cumulative=FALSE.

The returned occurrence matrix (plant growth forms against sites) can be converted to long format (with rows as individual occurrences of growth forms) using:

```
my.matrix <- growth_form_table(my.veg.PI, m_kind="percent_cover", cover_type="PFC")
library(reshape2)
my.matrix <- as.data.frame(melt(as.matrix(my.matrix)))
my.matrix <- my.matrix[-which(my.matrix$value == 0),]
```

The `round` function can be used on the returned matrix to estimate percent covers to the nearest percent if desired (i.e., with `digits=0`)

Value

Returns a data frame with plant growth forms as columns and sites as rows. Values are determined by argument `m_kind`. For 'PA', binary presence/absence (0/1) is returned; for 'richness', the numbers of species (integer) in growth form categories are returned; for 'percent_cover', percent cover from point-intercept is returned (see Details).

Author(s)

Greg R. Guerin, Samantha E.M. Munroe

References

NVIS Technical Working Group (2017) Australian Vegetation Attribute Manual: National Vegetation Information System, Version 7.0. Department of the Environment and Energy, Canberra. Prep by Bolton, M.P., deLacey, C. and Bossard, K.B. (Eds)

See Also

[get_ausplots](#)

[single_cover_value](#)

Examples

```
## Not run:
#get veg.PI data for selected plots:
my.data <- get_ausplots(my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002"),
  veg.PI=TRUE, site_info=FALSE)

#generate a percent cover occurrence matrix for plant growth forms:
growth_form_table(my.data$veg.PI, m_kind="percent_cover", cover_type="PFC",
  cumulative=FALSE, species_name="SN")

#calculate cover of strata:
growth_form_table(my.data$veg.PI, m_kind="percent_cover",
  cover_type="PFC", cumulative=FALSE, by_strata=TRUE, species_name="SN")

## End(Not run)
```

optim_species	<i>Optimisation methods for plot selection using different diversity indices in order to maximise species accumulation</i>
---------------	--

Description

This function applies different optimisation methods to select a subset of plots that maximise species accumulation. Optimisation methods vary based on the desired biodiversity parameters chosen by the user. The function operates under the 'Maximum covering problem' framework, which seeks to identify the plots that will protect the maximum number of species in a specified number of plots. The user specifies the number of plots to select, and each optimiser selects the plots that represent the largest number of species for that given number of plots.

Usage

```
optim_species(speciesVsitesMatrix, n.plt=250, richness=TRUE, RRR=TRUE,
              CWE=TRUE, shannon=TRUE, simpson=TRUE, simpson_beta=TRUE,
              start="fixed", plot_name= NULL, frequent=TRUE, random=FALSE,
              iterations=10, plot=TRUE, verbose=TRUE)
```

Arguments

speciesVsitesMatrix	dataframe or matrix, formatted as species (presence/absence or abundance) versus sites, where rows are sites and columns are species. See Details for more information on formatting.
n.plt	Number of plots, n, conforming the subset to be optimised.
richness	Species richness selected as optimiser. By default is TRUE.
RRR	Range rarity richness selected as optimiser. By default is TRUE.
CWE	Corrected Weight Endemism selected as optimiser. By default is TRUE.
shannon	Shannon-Wiener diversity index selected as optimiser. By default is TRUE.
simpson	Simpson diversity index selected as optimiser. By default is TRUE.
simpson_beta	Simpson dissimilarity selected as optimiser. By default is TRUE.
start	Choose under which condition the first plot for the simpson_beta optimiser is selected. The default, "fixed", uses the most speciose plot as the start seed. See details for additional options.
plot_name	Specific plot to start the optimisation when the user has selected start = "defined". By default, plot_name = NULL. If rownames are provided, the plot_name should be in character format and must match the relevant rowname in the input species matrix. If there are no rownames, plot_name can be numeric and will specify the row to use as the start seed.
frequent	See Details. By default is TRUE.

iterations	Number of random seed replications for simpson_beta if frequent=TRUE and also number of random replicates if random=TRUE.
random	Generation of a set of random species accumulations. By default is FALSE
plot	Whether or not to immediately plot the species accumulation curves for all the optimisers.
verbose	Logical, whether to print progress of iterations to the console.

Details

The input is a species versus sites matrix or dataframe. If a dataframe, the first column can list the site names. Site names must contain text, they cannot be numeric. Depending on the desired optimiser, the input data needs to be either species presence/absence or abundance. For richness, RRR, CWE, and simpson_beta optimisers, a presence/absence input matrix is required. For shannon and simpson optimisers, an abundance matrix is required. If the input data include abundance, the function automatically generates binary presence/absence data when required. TERN plot species occurrence matrices generated by the `ausplotsR` function `species_table` can be directly incorporated into optimiser function.

The `start` refers to the first plot used as the starting seed when using the simpson_beta optimiser. If "fixed", the plot with the greatest species richness is chosen as the start seed. If "random", a random plot is selected as the start seed. If "defined" the user assigns a specific starting plot as the start seed. Note that if `start = "defined"` then the `plot_name` argument must be provided.

`plot_name` must be provided when `start = "defined"` for the simpson_beta optimiser. If the input matrix or dataframe contains site names, then `plot_name` must match the rowname of the desired site to be used as the starting seed. If the input matrix does not include site names, then `plot_name` should specify the row number to be used as the starting seed.

`richness` refers to Species richness, which is the count of the number of species present in a given site. It is best used when the goal is to identify biodiversity hotspots.

RRR refers to Range rarity richness, which is a rarity-weighted richness calculated as the inverse of the number of sites in which a species occur. It is best used when the goal is to identify areas of high biodiversity and biological uniqueness.

CWE refers to Corrected Weight Endemism, which is calculated as range rarity richness (RRR) divided by species richness. It is best used when the goal is to identify centers of endemism highlighting range-restricted species.

`shannon` refers to the Shannon–Wiener diversity index, which combines species richness and the evenness or equitability by computing the species' relative abundances. The Shannon–Wiener diversity index assumes that all species are represented in a sample and that they are randomly sampled. The Shannon–Wiener index is defined as $H = -\sum_i p_i \log_b p_i$, where p_i is the proportional abundance of species i and b is the base of the logarithm. It is most popular to use natural logarithms, but some argue for base $b = 2$ (which makes sense, but no real difference).

`simpson` refers to the Simpson diversity index which combines species richness and the evenness or equitability by computing the species' relative abundances. The Simpson diversity index is a dominance index, giving more weight to common or dominant species. The Simpson diversity index is based on $D = \sum p_i^2$ and returns $1 - D$

`simpson_beta` refers to the Simpson dissimilarity, which is based on diversity partitioning, which separates species replacement (i.e. turnover) from species loss (i.e. nestedness). The Simpson

dissimilarity corresponds to the turnover component of the Sorensen dissimilarity. Thus, it is used to maximise species turnover.

By default, the function will extract and compile data from the top n selected plots (as specified by the user) based on all the different optimisers. The starting seed by default will be "fixed" which will correspond to the site with the highest value of species richness.

frequent refers to the most frequent sites that have been selected using the simpson_beta optimiser in a certain number of iterations that must be defined by the user. In order to do so, the starting seed for the simpson_beta optimiser must be "random". The result will display two different accumulation curves: one with the most frequent selected plots and another one with the mean and standard deviation of all the species accumulation curves obtained with a random starting seed for all the iterations

random refers to the species accumulation when the sites are selected randomly.

plot calls a function that allows plotting all the species accumulation curves obtained for each of the optimisers included in the optim_species function, see [plot_opt](#).

Value

Returns a list containing, for each optimiser within the function, a species accumulation object (see [specaccum](#), object as returned from vegan R package). The species accumulation refers to the cumulative curve or the number of species for a certain number of selected sites or individuals. Likewise, a list of the sites selected in order to maximise the value of the species accumulated using each optimiser will be returned. Additionally, the function will plot by default of the species cumulative curves obtained by the different optimisers.

Author(s)

Irene Martin-Fores, Samantha Munroe and Greg Guerin.

References

- Albuquerque, F. & Beier, P. (2015) Rarity-weighted richness: a simple and reliable alternative to integer programming and heuristic algorithms for minimum set and maximum coverage problems in conservation planning. *PLoS ONE* **10**, e0119905.
- Baselga, A. (2010) Multiplicative partition of true diversity yields independent alpha and beta components; additive partition does not. *Ecology* **91**, 1974-1981.
- Baselga, A. (2012) The relationship between species replacement, dissimilarity derived from nestedness, and nestedness. *Global Ecology and Biogeography* **21**, 1223-1232.
- Baselga, A. & Leprieur, F. (2015) Comparing methods to separate components of beta diversity. *Methods in Ecology and Evolution* **6**, 1069-1079.
- Guerin, G.R. & Lowe, A.J. (2015) 'Sum of inverse range-sizes' (SIR), a biodiversity metric with many names and interpretations. *Biodiversity and conservation* **24**, 2877-2882.
- Guerin, G.R., Ruokolainen, L. & Lowe, A.J. (2015). A georeferenced implementation of weighted endemism. *Methods in Ecology and Evolution* **6**, 845-852.
- Jost, L. (2007). Partitioning diversity into independent alpha and beta components. *Ecology* **88**, 2427-2439.

Koleff, P., Gaston, K. J., & Lennon, J. J. (2003). Measuring beta diversity for presence-absence data. *Journal of Animal Ecology* **72**, 367-382.

Martín-Forés, I., Guerin, G. R., Munroe, S. E., & Sparrow, B. (2021). Applying conservation reserve design strategies to define ecosystem monitoring priorities. *Ecology and Evolution* **11**, 17060-17070.

Oksanen, J. et al. (2016) vegan: Community Ecology Package. R package version 2.4-3. Vienna: R Foundation for Statistical Computing.

See Also

[plot_opt](#)

[specaccum](#)

[fisher.alpha](#)

Examples

```
#example with dune database from vegan
library(vegan)
data(dune)

optim_species(dune, n.plt=15, frequent=FALSE)

#example with auplots database from ausplotsR
## Not run:
library(ausplotsR)

ausplotsdata <- get_ausplots(veg.PI=TRUE)

ausplotsPAdata <- species_table(ausplotsdata$veg.PI, m_kind="percent_cover",
cover_type="PFC", species_name="SN")

optim_species(ausplotsPAdata, n.plt=5, iterations= 5)

optim_species(ausplotsPAdata, n.plt=5, start="defined", plot=TRUE,
plot_name="WAANUL0001-56966", frequent=FALSE, random=TRUE, iterations=20)

## End(Not run)
```

plot_opt

Plot a set of species accumulation curves together

Description

This function plots different species accumulation curves obtained through different optimisers in the [optim_species](#) function.

Usage

```
plot_opt(optim_result, choices=c("Richness", "RRR", "CWE", "Shannon",  
"Simpson", "SimpsonBeta", "Frequent", "SimpsonBeta_randSeed", "Random"))
```

Arguments

optim_result	Object returned from the optim_species function, which is a list of species accumulation objects (see specaccum) obtained with the different optimisers.
choices	select the optimisers from which the species accumulations curves are going to be plotted. The choices can be "Richness", "RRR", "CWE", "Shannon", "Simpson", "SimpsonBeta", "Frequent", "SimpsonBeta_randSeed", "Random"

Details

Line colours are assigned randomly on each run.

Value

This function will return a plot of the species cumulative curves obtained by the different optimisers in the [optim_species](#) function.

Author(s)

Greg R. Guerin

See Also

[optim_species](#)

Examples

```
#example with dune database from vegan  
library(vegan)  
data(dune)  
  
example1 <- optim_species(dune, n.plt=15, frequent=FALSE, plot=FALSE)  
  
plot_opt(example1)  
plot_opt(example1, choices=c("Richness", "SimpsonBeta"))  
  
#example with aplots database from ausplotsR  
## Not run:  
library(ausplotsR)  
  
ausplotsdata <- get_ausplots(veg.PI=TRUE)  
ausplotsPAdata <- species_table(ausplotsdata$veg.PI, m_kind="PA",  
species_name="SN")  
  
example2 <- optim_species(ausplotsPAdata, n.plt=5, iterations=5, plot=FALSE)  
plot_opt(example2)  
plot_opt(example2,
```

```

choices=c("RRR", "SimpsonBeta", "Frequent", "SimpsonBeta_randSeed"))

## End(Not run)

```

single_cover_value *Vegetation cover by height or growth form using TERN AusPlots data.*

Description

Calculates a single vegetation cover value per site based on the plot-based point-intercept data from AusPlots (as generated by [get_ausplots](#)). Cover can be subsetted to vegetation that has a specified minimum or maximum height and/or by plant growth forms, allowing user defined definitions of e.g. grass or tree cover. For example, by default, forest cover is calculated per plot for tree growth forms of 5 metres or higher.

Usage

```

single_cover_value(veg.PI, in_canopy_sky=FALSE,
by.growth_form=TRUE, min.height=5, max.height=NULL,
my.growth_forms=c("Tree/Palm", "Tree Mallee"))

```

Arguments

veg.PI	The input raw point intercept data (\$veg.PI) as generated in the get_ausplots function.
in_canopy_sky	Logical, whether to include in canopy sky hits to calculate 'opaque canopy cover' instead of 'projected foliage cover'. Set to TRUE to calculate opaque canopy cover (e.g., suitable for some applications such as comparison to remotely sensed cover products).
by.growth_form	Logical, whether to subset by plant growth form. If set to FALSE then only height subsetting occurs. Set to TRUE to calculate cover subsetted to specified growth forms.
min.height	Numeric, sets the height in m below which PI hits are ignored. This argument is used to calculate e.g. cover of trees 5 m high or higher. Can be set to zero to ignore height and include any plant hit. If you set min.height to a negative number you will get a nonsensical output!
max.height	Numeric, sets the height in m above which PI hits are ignored. This argument can be used to calculate ground cover of desired growth forms, for example.
my.growth_forms	A user-supplied character vector specifying growth forms to include in the cover calculation. Defaults to trees. Applies only when by.growth_form=TRUE, otherwise this argument is ignored and only the height rule is applied. For allowable growth forms, see <code>unique(veg.PI\$growth_form)</code> .

Details

All included point intercept hits are merged to give a single percent cover value with a maximum of 100. Cover partitioned by multiple plant growth forms can be calculated using `growth_form_table`, by species using `species_table` and fractional (green, brown or bare) cover using `fractional_cover`. Note, when `min.height` is set to zero and `by.growth_form` is set to `FALSE`, the output is nearly the same as the green cover fraction returned from `fractional_cover`. The values can differ, however, because `fractional_cover` applies a height rule in which the highest intercept at a given point is taken, whereas `single_cover_value` finds any green cover, leading to differences, most obviously, for example, when dead trees overhang green understorey. For such general cover purposes, we recommend `fractional_cover`. `single_cover_value` is best suited to cover subset by height and growth form.

Value

Returns a data.frame in which plots are rows identified by a unique site and visit identifier ('site_unique') and the returned cover value is given in the percentCover column.

Author(s)

Greg Guerin

See Also

[get_ausplots](#)

[fractional_cover](#)

Examples

```
## Not run:
my.dat <- get_ausplots(bounding_box=c(140, 142, -20, -18), veg.PI=TRUE,
site_info=FALSE)

#Default settings, where cover of trees 5 m or higher is calculated:
tree.cover <- single_cover_value(my.dat$veg.PI)
tree.cover

#Tussock grasses of any height (minimum height set to zero):
grass.cover <- single_cover_value(my.dat$veg.PI,
my.growth_forms=c("Tussock grass"), min.height=0)
grass.cover

#Any green veg at least 2 m in height:
veg.height.eg <- single_cover_value(my.dat$veg.PI, by.growth_form=FALSE,
min.height=2)
veg.height.eg

#Any green veg up to 1 m high:
ground.cover <- single_cover_value(my.dat$veg.PI, by.growth_form=FALSE,
min.height=0, max.height=1)
ground.cover
```

```
## End(Not run)
```

species_list	<i>Species lists for AusPlots</i>
--------------	-----------------------------------

Description

Nice species lists based on the vegetation voucher module of Ausplots generated using the [get_ausplots](#) function.

Usage

```
species_list(veg.vouch, grouping=c("by_site", "by_visit", "collapse"),
  species_name=c("SN", "HD", "GS"), strip_bryophytes=FALSE,
  append_family=FALSE, writefile=FALSE, outfile="my_species_lists.txt")
```

Arguments

veg.vouch	The input raw plant voucher data generated by get_ausplots
grouping	One of c("by_site", "by_visit", "collapse"). Determines whether species names are pooled over all visits to each plot (site_location_name, the default), or gathered by individual site visits (site_unique). The final option 'collapse' returns a complete list of species over the plots provided.
species_name	Defaults to "SN" (standardised_name); set to "HD" to use "herbarium_determination", and "GS" to use standardised "genus_species" format. See details for an explanation of each setting.
strip_bryophytes	Logical. Switch to TRUE to exclude bryophyte records and only return vascular plants in Angiosperm (flowering plants), Gymnosperm (conifers) and Pteridophyte (ferns and allies) groups. Although there are a number of bryophyte records in Ausplots, they are not surveyed systematically.
append_family	Logical. If set to TRUE, names in the the returned species lists are appended with (and sorted by) family standardised name.
writefile	Logical. Whether or not to write the result to a text file.
outfile	Character denoting path/file/extension to attempt to write to if writefile=TRUE.

Details

The aim of the function is to provide simple, cleaned lists of species that have been recorded at various Ausplots sites, simplifying from the more detailed voucher and identification information in the \$veg.vouch vegetation voucher module. The output is not designed for downstream analysis (which is perhaps better performed by manipulating the raw data tables) but as a rapid means of viewing recorded species.

species_name provides multiple options for how names are presented. If species_name="HD", the function will use the "herbarium_determination" provided by state herbaria to identify unique

species. Herbarium determinations are made to the lowest possible taxonomic rank, which may be the family, genus, species, subspecies or variety. If `species_name="SN"`, the default, the function will use the `"standardised_name"` to identify unique species. Values are based on the `veg.PI$herbarium_determination` but have been matched to the accepted scientific name according to the Australian Plant Census (APC: <https://www.anbg.gov.au/cpbr/program/hc/hc-APC.html>) and the Australian Plant Name Index (APNI: <https://www.anbg.gov.au/cpbr/program/hc/hc-APNI.html>). The standardised name field therefore helps to ensure taxonomic consistency. It excludes any records that don't match the APC. If `species_name="GS"`, only the standardised genus species rank ("`genus_species`" in the `veg.vouch` input table) is used to identify species. `species_name="GS"` maximises consistency in species comparisons between plots, but reduces the taxonomic detail.

Value

Returns a list containing a character vector of species names for each plot/visit grouping. If `grouping="collapse"`, a single character vector is returned. If `writefile=TRUE`, a text file is written to path `outfile` in the working directory.

Author(s)

Greg Guerin, Samantha Munroe

See Also

[get_ausplots](#)

[species_table](#)

Examples

```
## Not run:
#get veg.vouch data for selected plots:
my.data <- get_ausplots(site_info=FALSE, veg.vouchers=TRUE,
my.Plot_IDs=c("SAAFLB0005", "SAAFLB0006"))

#generate 'genus_species' lists by site:
species_list(my.data$veg.vouch, grouping="by_site",
species_name="GS", writefile=FALSE)

#generate a complete species list ordered by family:
species_list(my.data$veg.vouch, grouping="collapse",
species_name="SN", append_family=TRUE, writefile=FALSE)

## End(Not run)
```

species_table *Species occurrence matrices for AusPlots*

Description

This function takes a data frame of individual raw point-intercept hits from AusPlots generated using the [get_ausplots](#) function, and generates species occurrence matrices as desired based on presence/absence, cover, frequency or IVI.

Usage

```
species_table(veg.PI, m_kind=c("PA", "percent_cover", "freq", "IVI"),
  cover_type=c("PFC", "OCC"), species_name=c("SN", "HD", "GS"),
  strip_bryophytes=FALSE)
```

Arguments

veg.PI	The input raw point-intercept data generated by get_ausplots
m_kind	The desired species scoring method: PA: binary (presence/absence), percent cover, frequency (based on occurrences on the 10 point-intercept transects within plots) or IVI (combination of cover and frequency - see Details).
cover_type	A choice between PFC: 'projected foliage cover' and OCC: 'opaque canopy cover' and only applies to percent_cover and IVI. If 'PFC' is selected (the default), hits scored as 'in canopy sky' are removed, whereas they are retained as cover for that species for 'OCC'. 'PFC' may be more suitable for some applications such as comparison to remotely sensed cover products.
species_name	Set to "SN" to use "standardised_names" (the default), "HD" to use "herbarium_determination", and "GS" to use "genus_species" See details for an explanation of each setting.
strip_bryophytes	Logical. Switch to TRUE to exclude bryophyte records and only return vascular plants in Angiosperm (flowering plants), Gymnosperm (conifers) and Pteridophyte (ferns and allies) groups. Although there are a number of bryophyte records in Ausplots, they are not surveyed systematically.

Details

Species occurrence matrices are the basis for a wide range of downstream analyses in community ecology, such as classification, ordination, alpha and beta diversity, abundance distributions and many more. Many of these analyses can be performed in the vegan R package using the returned matrix.

IVI (Importance Value Index; Ellenberg & Mueller-Dombois 1974) is calculated as the sum of relative abundance (percent cover) and relative frequency (percent frequency of occurrence on the 10 transects used to gather the point-intercept data). It has a theoretical range of 0 - 200 and is calculated as follows:

$$(cover/totalcover) * 100 + (frequency/totalfrequency) * 100$$

species_name provides multiple options for calculating plant cover, presence or frequency. If species_name="HD", the function will use the "herbarium_determination" provided by state herbaria to identify unique species. "herbarium_determination" are made to the lowest possible taxonomic rank, which may be the family, genus, species, subspecies or variety. If species_name="SN", the default, the function will use the "standardised_name" to identify unique species. Values are based on the veg.PI\$herbarium_determination but have been matched to the accepted scientific name according to the Australian Plant Census (APC: <https://www.anbg.gov.au/cpbr/program/hc/hc-APC.html>) and the Australian Plant Name Index (APNI: <https://www.anbg.gov.au/cpbr/program/hc/hc-APNI.html>). The standardised name field therefore helps to ensure taxonomic consistency. It excludes any records that don't match the APC. If species_name="GS", only the standardised genus species rank (i.e., "genus_species" in the veg.PI input table) is used to identify species. species_name="GS" maximises consistency in species comparisons between plots, but reduces the taxonomic detail.

The returned occurrence matrix (species against sites) can be converted to 'long' format (with rows as species records) using:

```
my.matrix <- species_table(my.veg.PI, m_kind="PA", cover_type="PFC")
library(reshape2)
my.matrix <- as.data.frame(melt(as.matrix(my.matrix)))
my.matrix <- my.matrix[~which(my.matrix$value == 0),]
```

The [round](#) function can be used on the returned matrix to estimate percent covers to the nearest percent if desired (i.e., with digits=0)

Value

Returns a data frame with species as columns and sites as rows. Values are determined by argument m_kind.

Author(s)

Greg R. Guerin, Samantha E.M. Munroe

References

Ellenberg, D. & Mueller-Dombois, D. (1974) Aims and methods of vegetation ecology. Wiley, New York, NY.

See Also

[get_ausplots](#)

Examples

```
## Not run:  
#get veg.PI data for selected plots:  
my.data <- get_ausplots(my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002"),  
  veg.PI=TRUE, site_info=FALSE)  
  
#generate a percent cover occurrence matrix using "genus_species" species identification:  
species_table(my.data$veg.PI, m_kind="percent_cover", cover_type="PFC",  
  species_name="GS")  
  
## End(Not run)
```

Index

ausplots_trajectory, [4](#), [5](#), [9](#)
ausplots_visual, [4](#), [7](#), [7](#)
ausplotsR (ausplotsR-package), [2](#)
ausplotsR-package, [2](#)

basal_area, [4](#), [10](#)

fisher.alpha, [22](#)
fractional_cover, [4](#), [8](#), [9](#), [11](#), [25](#)

get_ausplots, [3–12](#), [13](#), [16](#), [18](#), [24–29](#)
growth_form_table, [4](#), [9](#), [16](#)

map_ausplots (ausplots_visual), [7](#)

optim_species, [4](#), [19](#), [22](#), [23](#)

plot_opt, [21](#), [22](#), [22](#)

round, [18](#), [29](#)

single_cover_value, [4](#), [9](#), [18](#), [24](#)
specaccum, [21–23](#)
species_list, [4](#), [26](#)
species_table, [4](#), [9](#), [14](#), [15](#), [20](#), [27](#), [28](#)